



PRODUCT OVERVIEW

A fully potted 2-bank charger offering 10A charging of 36V lithium batteries on both banks for fast, efficient charging of multi-battery systems. Lithium battery wake functionality and comprehensive safety protections deliver dependable charging in demanding marine environments.

2 YEAR LIMITED WARRANTY

Reliable coverage for lasting confidence.

10A CHARGING PER BANK

Fast & efficient 10A charging.

LITHIUM WAKE FUNCTION

Wake deeply discharged lithium batteries.

TIGER LITHIUM™ OPTIMIZED

Maximize Tiger Lithium™ battery performance.

IP67 PROTECTION

Fully potted for demanding environments.

FAST CHARGING 36V DUAL-BATTERY SYSTEM

APPLICATIONS



BASS BOATS



INSHORE BOATS



OFFSHORE BOATS



YACHTS



OVERLAND & RV

2-YEAR LIMITED WARRANTY

UNMATCHED RELIABILITY. TOTAL PEACE OF MIND.

Built for dependable charging and backed by Tiger Lithium support for lasting peace of mind.

TECHNICAL DASHBOARD

Quick answers to the most important questions.



ELECTRICAL

AC Input Voltage	AC 105-125V, 60 Hz
Power Cord Plug	3-Prong Grounded
Power Cord Length	5 ft / 1.52 m
Charging Leads Length	6 ft / 1.83 m
Output Ring Terminals	5/16 in / 8mm



CHARGING PROFILES

36V Lithium	43.2 V +0.2V Peak Voltage
-------------	---------------------------



CHARGING

Bank 1	36V Lithium @ 10A
Bank 2	36V Lithium @ 10A



PHYSICAL

Weight	17.1 lb (7.75 kg)
Case Material	Cast Aluminum
Ingress Protection	IP67
Cooling Fan	Thermostat-Controlled
Dimensions	11.5 x 9.5 x 4 in 292 x 241 x 102 mm



CHARGER PROTECTION

Battery Detection	Automatic
Reverse-Polarity Protection	Integrated
Over-Temp Protection	Automatic
Short-Circuit Protection	Integrated
Over-Voltage Protection	Automatic
No-Load Output	Disabled



KEY ADVANTAGES

- ✓ Charges two 36V lithium batteries
- ✓ 10A maximum charging output per bank
- ✓ Fully potted for protection against moisture and vibration
- ✓ Lithium battery wake functionality
- ✓ Safe battery detection before charging begins
- ✓ Integrated thermostat-controlled cooling fan
- ✓ Pre-installed ATM inline fuse holders and fuses



PRODUCT NOTES

Banks 1 and 2 support 36V lithium charging. Compatible with Tiger Lithium™ batteries and other lithium batteries requiring the specified charging voltage. Includes pre-installed output leads, ring terminals, ATM inline fuse holders, and fuses. Refer to the User Manual before installation.



SUPPORTED BATTERIES

Bank 1	(Qty. 1) 36V Lithium Battery
Bank 2	(Qty. 1) 36V Lithium Battery

Confirm battery-charger voltage compatibility before use.



CERTIFICATIONS

NOM NYCE • RoHS • CE